

P/N MS14101-4CP

Military-Fasteners.com

Description

MS14101 series bearing, Plastic polytetrafluoroethylene MS14101-4CP

* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

Order this part online

Additional Information

SKU / Model:	MS141014CP
Minimum Qty (MOQ):	1
NSN:	3120-01-566-0556
Schedule B:	8482.10.1080
ECCN:	EAR99



P/N MS14101-4CP Specifications

Bore Diameter:	0.2495 Inches Minimum And 0.2500 Inches Maximum
Outer Member Outside Diameter:	0.6557 Inches Minimum And 0.6562 Inches Maximum
Outer Member Width:	0.2450 Inches Minimum And 0.2550 Inches Maximum
Inner Member Width:	0.3410 Inches Minimum And 0.3430 Inches Maximum
Static Radial Load Rating:	6040 Pounds
Hardness Rating:	28.0 Rockwell C Minimum Outer Race Member And 37.0 Rockwell C Maximum Outer Race Member
Hardness Rating:	43.0 Rockwell C Minimum Inner Member And 47.0 Rockwell C Maximum Inner Member
Material:	Plastic Polytetrafluoroethylene Race Liner
Material:	Steel Comp Xm-13 Inner Member
Material:	Steel Comp 630 Outer Race Member
Surface Treatment:	Passivate Inner Member
Surface Treatment:	Passivate Outer Race Member
Style Designator:	With Insert And/or Liner With Staking Groove

How to Order

Order this plain self-aligning bearing from our inventory online by visiting <u>https://military-fasteners.com/bearings/plain+self_aligning+bearings/MS14101-4CP</u> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out<u>here</u> to complete your order.