



Military-Fasteners.com

P/N MS14101-5A

Description

Inner diameter: 5/16" outer diameter: 3/4", self-lubricating, self-aligning, low speed, narrow, grooved outer ring, MS14101 series bearing

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

Alternate Part Numbers

[03-825-05](tel:03-825-05)

SKU / Model:	MS141015A
Minimum Qty (MOQ):	1
NSN:	3120-01-064-6301
ECCN:	EAR99
National Motor Freight:	114850, Bearing / Bushing O / T Ball / Roller I / S



P/N MS14101-5A Specifications

Bore Diameter:	0.3120 Inches Minimum And 0.3125 Inches Maximum
Outer Member Outside Diameter:	0.7495 Inches Minimum And 0.7500 Inches Maximum
Outer Member Width:	0.2760 Inches Minimum And 0.2860 Inches Maximum
Inner Member Width:	0.3730 Inches Minimum And 0.3750 Inches Maximum
Static Radial Load Rating:	8750 Pounds
Special Features:	0.6620 In. Dia Center Of Staking Groove
Material:	Steel Comp 440c Inner Member
Material:	Steel Comp 630 Outer Ring
Material Document And Classification:	Ams 5630 Assn Std Single Material Response Inner Member
Material Document And Classification:	Ams 5643 Assn Std Single Material Response Outer Ring
Style Designator:	With Insert And/or Liner With Staking Groove

How to Order

Order this plain self-aligning bearing from our inventory online by visiting https://military-fasteners.com/bearings/plain+self_aligning+bearings/MS14101-5A and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.