

Description

Inner diameter: 3/8" outer diameter: 13/16", self lubricating, self aligning, low speed, narrow, grooved outer ring, MS14101 series bearing

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information**Alternate Part Numbers**

[03-825-06](tel:03-825-06)

| | |
|-------------------------|---|
| SKU / Model: | MS141016 |
| Minimum Qty (MOQ): | 2 |
| NSN: | 3120-01-006-9149 |
| Schedule B: | 7318.15.5030 |
| ECCN: | EAR99 |
| National Motor Freight: | 114850, Bearing / Bushing O / T Ball / Roller I / S |



P/N MS14101-6 Specifications

| | |
|---------------------------------------|---|
| Bore Diameter: | 0.3745 Inches Minimum And 0.3750 Inches Maximum |
| Outer Member Outside Diameter: | 0.8120 Inches Minimum And 0.8125 Inches Maximum |
| Outer Member Width: | 0.3070 Inches Minimum And 0.3170 Inches Maximum |
| Inner Member Width: | 0.4040 Inches Minimum And 0.4060 Inches Maximum |
| Static Radial Load Rating: | 10540 Pounds |
| Hardness Rating: | 23.0 Rockwell C Minimum Outer Race Member And 35.0 Rockwell C Maximum Outer Race Member |
| Hardness Rating: | 55.0 Rockwell C Minimum Inner Member And 62.0 Rockwell C Maximum Inner Member |
| Material: | Plastic Polytetrafluoroethylene Race Liner |
| Material: | Steel Comp 440c Inner Member |
| Material: | Steel Comp 630 Outer Race Member |
| Style Designator: | With Insert And/or Liner With Staking Groove |

How to Order

Order this plain self-aligning bearing from our inventory online by visiting https://military-fasteners.com/bearings/plain+self_aligning+bearings/MS14101-6 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.