

Description

single row

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

Alternate Part Numbers

[03-825-06K](#)

SKU / Model:	MS141016K
Minimum Qty (MOQ):	1
NSN:	3120-01-491-4872
ECCN:	2A991.e



* See page 2 for technical characteristics

P/N MS14101-6K Specifications

Bore Diameter:	0.3745 Inches Minimum And 0.3750 Inches Maximum
Outer Member Outside Diameter:	0.8120 Inches Minimum And 0.8125 Inches Maximum
Outer Member Width:	0.3070 Inches Minimum And 0.3170 Inches Maximum
Inner Member Width:	0.4040 Inches Minimum And 0.4060 Inches Maximum
Hardness Rating:	28.0 Rockwell C Minimum Outer Race Member And 37.0 Rockwell C Maximum Outer Race Member
Hardness Rating:	55.0 Rockwell C Minimum Inner Member And 62.0 Rockwell C Maximum Inner Member
Special Features:	Low Break-away Torque
Material:	Plastic Polytetrafluoroethylene Race Liner
Material:	Steel Comp 440c Inner Member
Surface Treatment:	Anodize Inner Member
Style Designator:	With Insert And/or Liner With Staking Groove

How to Order

Order this plain self-aligning bearing from our inventory online by visiting https://military-fasteners.com/bearings/plain+self_aligning+bearings/MS14101-6K and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.