

**Description**

single row

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

**Alternate Part Numbers**

[03-825-06K](#)

SKU / Model:	MS141016K
Minimum Qty (MOQ):	1
NSN:	3120-01-491-4872
ECCN:	2A991.e



## P/N MS14101-6K Specifications

<b>Bore Diameter:</b>	0.3745 Inches Minimum And 0.3750 Inches Maximum
<b>Outer Member Outside Diameter:</b>	0.8120 Inches Minimum And 0.8125 Inches Maximum
<b>Outer Member Width:</b>	0.3070 Inches Minimum And 0.3170 Inches Maximum
<b>Inner Member Width:</b>	0.4040 Inches Minimum And 0.4060 Inches Maximum
<b>Hardness Rating:</b>	28.0 Rockwell C Minimum Outer Race Member And 37.0 Rockwell C Maximum Outer Race Member
<b>Hardness Rating:</b>	55.0 Rockwell C Minimum Inner Member And 62.0 Rockwell C Maximum Inner Member
<b>Special Features:</b>	Low Break-away Torque
<b>Material:</b>	Plastic Polytetrafluoroethylene Race Liner
<b>Material:</b>	Steel Comp 440c Inner Member
<b>Surface Treatment:</b>	Anodize Inner Member
<b>Style Designator:</b>	With Insert And/or Liner With Staking Groove

## How to Order

Order this plain self-aligning bearing from our inventory online by visiting [https://military-fasteners.com/bearings/plain+self\\_aligning+bearings/MS14101-6K](https://military-fasteners.com/bearings/plain+self_aligning+bearings/MS14101-6K) and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.