

Description

single row, self aligning

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	MS141018P
Minimum Qty (MOQ):	1
NSN:	3120-01-330-9912
ECCN:	EAR99
National Motor Freight:	114850, Bearing / Bushing O / T Ball / Roller I / S



* See page 2 for technical characteristics

P/N MS14101-8P Specifications

Bore Diameter:	0.4995 Inches Minimum And 0.5000 Inches Maximum
Outer Member Outside Diameter:	0.9995 Inches Minimum And 1.0000 Inches Maximum
Outer Member Width:	0.3850 Inches Minimum And 0.3950 Inches Maximum
Inner Member Width:	0.4980 Inches Minimum And 0.5000 Inches Maximum
Hardness Rating:	28.0 Rockwell C Minimum Outer Race Member And 37.0 Rockwell C Maximum Outer Race Member
Hardness Rating:	55.0 Rockwell C Minimum Inner Member And 62.0 Rockwell C Maximum Inner Member
Material:	Plastic Polytetrafluoroethylene Bore Liner
Material:	Steel Comp 440c Inner Member
Material:	Steel Comp 630 Outer Race Member
Material Document And Classification:	Ams 5630 Assn Std Single Material Response Inner Member
Material Document And Classification:	Ams 5643 Assn Std Single Material Response Outer Race Member
Surface Treatment:	Cadmium Outer Race Member And Chromate Outer Race Member
Surface Treatment Document And Classification:	Qq-p-416,ty 2,cl 2 Fed Spec Single Treatment Response Outer Race Member
Style Designator:	With Insert And/or Liner With Staking Groove

How to Order

Order this plain self-aligning bearing from our inventory online by visiting https://military-fasteners.com/bearings/plain+self_aligning+bearings/MS14101-8P and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.