

P/N MS14101-9

Description

non lubricated, MS14101 series bearing

* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

Order this part online

Additional Information

Alternate Part Numbers

THT9V

SKU / Model: MS141019

Minimum Qty (MOQ):

NSN: 3120-01-033-2773

Schedule B: 8482.10.5068

ECCN: EAR99

National Motor Freight: 133300, Machinery / Machines Noi









P/N MS14101-9 Specifications

Bore Diameter:	0.5620 Inches Minimum And 0.5625 Inches Maximum
Outer Member Outside Diameter:	1.0932 Inches Minimum And 1.0937 Inches Maximum
Outer Member Width:	0.4320 Inches Minimum And 0.4420 Inches Maximum
Inner Member Width:	0.5600 Inches Minimum And 0.5620 Inches Maximum
Static Radial Load Rating:	23200 Pounds
Hardness Rating:	28.0 Rockwell C Minimum Outer Race Member And 37.0 Rockwell C Maximum Outer Race Member
Hardness Rating:	55.0 Rockwell C Minimum Inner Member And 62.0 Rockwell C Maximum Inner Member
Material:	Plastic Polytetrafluoroethylene Race Liner
Material:	Steel Comp 440c Inner Member
Style Designator:	With Insert And/or Liner With Staking Groove

How to Order

Order this plain self-aligning bearing from our inventory online by visiting https://military-fasteners.com/bearings/plain+self_aligning+bearings/MS14101-9 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check outhere to complete your order.