

Description

non lubricated, MS14101 series bearing

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information****Alternate Part Numbers**[THT9V](#)

| | |
|-------------------------|----------------------------------|
| SKU / Model: | MS141019 |
| Minimum Qty (MOQ): | 1 |
| NSN: | 3120-01-033-2773 |
| Schedule B: | 8482.10.5068 |
| ECCN: | EAR99 |
| National Motor Freight: | 133300, Machinery / Machines Noi |



* See page 2 for technical characteristics

P/N MS14101-9 Specifications

| | |
|---------------------------------------|---|
| Bore Diameter: | 0.5620 Inches Minimum And 0.5625 Inches Maximum |
| Outer Member Outside Diameter: | 1.0932 Inches Minimum And 1.0937 Inches Maximum |
| Outer Member Width: | 0.4320 Inches Minimum And 0.4420 Inches Maximum |
| Inner Member Width: | 0.5600 Inches Minimum And 0.5620 Inches Maximum |
| Static Radial Load Rating: | 23200 Pounds |
| Hardness Rating: | 28.0 Rockwell C Minimum Outer Race Member And 37.0 Rockwell C Maximum Outer Race Member |
| Hardness Rating: | 55.0 Rockwell C Minimum Inner Member And 62.0 Rockwell C Maximum Inner Member |
| Material: | Plastic Polytetrafluoroethylene Race Liner |
| Material: | Steel Comp 440c Inner Member |
| Style Designator: | With Insert And/or Liner With Staking Groove |

How to Order

Order this plain self-aligning bearing from our inventory online by visiting https://military-fasteners.com/bearings/plain+self_aligning+bearings/MS14101-9 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.