

Description

inner diameter: 5/16" outer diameter: 11/16", self lubricating, self aligning, low speed, wide, chamfered outer ring,

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS141025
Minimum Qty (MOQ):	1
NSN:	3120-01-054-4693
Schedule B:	8482.10.1080
ECCN:	EAR99
National Motor Freight:	114850, Bearing / Bushing O / T Ball / Roller I / S



* See page 2 for technical characteristics

P/N MS14102-5 Specifications

Bore Diameter:	0.3120 Inches Minimum And 0.3125 Inches Maximum
Outer Member Outside Diameter:	0.6870 Inches Minimum And 0.6875 Inches Maximum
Outer Member Width:	0.3120 Inches Minimum And 0.3220 Inches Maximum
Inner Member Width:	0.4350 Inches Minimum And 0.4370 Inches Maximum
Static Radial Load Rating:	9400 Pounds
Part Name Assigned By Controlling Agency:	Bearing, Plain, Self Lubricating, Self-aligning, Low Speed, Wide, Chamfered, Outer Ring -65 Degrees To 325 Degrees
Material:	Steel Comp 440c Inner Member
Material:	Steel Comp 630 Outer Ring
Material Document And Classification:	Ams 5630 Assn Std Single Material Response Inner Member
Material Document And Classification:	Ams 5643 Assn Std Single Material Response Outer Ring
Style Designator:	With Insert And/or Liner

How to Order

Order this plain self-aligning bearing from our inventory online by visiting https://military-fasteners.com/bearings/plain+self_aligning+bearings/MS14102-5 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.