



Military-Fasteners.com

P/N MS14102-8

Description

inner diameter: 1/2", outer diameter: 1", plain, self, lubricating, self-aligning, low speed, wide, chamfered outer ring, -65 degrees to 325 degrees

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

Alternate Part Numbers

[03-824-08](tel:03-824-08)

SKU / Model:	MS141028
Minimum Qty (MOQ):	1
NSN:	3120-01-084-9242
ECCN:	EAR99
National Motor Freight:	114850, Bearing / Bushing O / T Ball / Roller I / S



* See page 2 for technical characteristics

P/N MS14102-8 Specifications

Bore Diameter:	0.4995 Inches Minimum And 0.5000 Inches Maximum
Outer Member Outside Diameter:	0.9995 Inches Minimum And 1.0000 Inches Maximum
Outer Member Width:	0.5000 Inches Minimum And 0.5100 Inches Maximum
Inner Member Width:	0.6230 Inches Minimum And 0.6250 Inches Maximum
Static Radial Load Rating:	21400 Pounds
Hardness Rating:	23.0 Rockwell C Minimum Outer Race Member And 35.0 Rockwell C Maximum Outer Race Member
Hardness Rating:	55.0 Rockwell C Minimum Inner Member And 62.0 Rockwell C Maximum Inner Member
Material:	Plastic Race Liner
Material:	Steel Inner Member
Material:	Steel Outer Race Member
Style Designator:	With Insert And/or Liner

How to Order

Order this plain self-aligning bearing from our inventory online by visiting https://military-fasteners.com/bearings/plain+self_aligning+bearings/MS14102-8 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.