

**Description**

inner diameter: 1/4" outer diameter: 5/8", self-lubricating, self-aligning, low speed, wide, grooved outer ring, -65 degrees to 325 degrees, MS14103 series bearing

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information****Alternate Part Numbers**

[03-826-04](#)

SKU / Model:	MS141034
Minimum Qty (MOQ):	2
NSN:	3120-01-024-4919
Schedule B:	8482.10.1080
ECCN:	EAR99
National Motor Freight:	133300, Machinery / Machines Noi



## P/N MS14103-4 Specifications

<b>Bore Diameter:</b>	0.2495 Inches Minimum And 0.2500 Inches Maximum
<b>Lubrication Material:</b>	Lubricant, Manufacturers Standard
<b>Outer Member Outside Diameter:</b>	0.6245 Inches Minimum And 0.6250 Inches Maximum
<b>Outer Member Width:</b>	0.3220 Inches Minimum And 0.3320 Inches Maximum
<b>Inner Member Width:</b>	0.4350 Inches Minimum And 0.4370 Inches Maximum
<b>Static Radial Load Rating:</b>	9000 Pounds
<b>Hardness Rating:</b>	55.0 Rockwell C Minimum Inner Member And 62.0 Rockwell C Maximum Inner Member
<b>Material:</b>	Plastic Polytetrafluoroethylene Race Liner
<b>Material:</b>	Steel Comp 440c Inner Member
<b>Material:</b>	Steel Comp 630 Outer Race Member
<b>Style Designator:</b>	With Insert And/or Liner With Staking Groove

## How to Order

Order this plain self-aligning bearing from our inventory online by visiting [https://military-fasteners.com/bearings/plain+self\\_aligning+bearings/MS14103-4](https://military-fasteners.com/bearings/plain+self_aligning+bearings/MS14103-4) and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.