



Military-Fasteners.com

P/N MS14103-4

## Description

inner diameter: 1/4" outer diameter: 5/8", self-lubricating, self-aligning, low speed, wide, grooved outer ring, -65 degrees to 325 degrees, MS14103 series bearing

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

## Additional Information

### Alternate Part Numbers

[03-826-04](#)

SKU / Model:	MS141034
Minimum Qty (MOQ):	2
NSN:	3120-01-024-4919
Schedule B:	8482.10.1080
ECCN:	EAR99
National Motor Freight:	133300, Machinery / Machines Noi



# P/N MS14103-4 Specifications

Bore Diameter:	0.2495 Inches Minimum And 0.2500 Inches Maximum
Lubrication Material:	Lubricant, Manufacturers Standard
Outer Member Outside Diameter:	0.6245 Inches Minimum And 0.6250 Inches Maximum
Outer Member Width:	0.3220 Inches Minimum And 0.3320 Inches Maximum
Inner Member Width:	0.4350 Inches Minimum And 0.4370 Inches Maximum
Static Radial Load Rating:	9000 Pounds
Hardness Rating:	55.0 Rockwell C Minimum Inner Member And 62.0 Rockwell C Maximum Inner Member
Material:	Plastic Polytetrafluoroethylene Race Liner
Material:	Steel Comp 440c Inner Member
Material:	Steel Comp 630 Outer Race Member
Style Designator:	With Insert And/or Liner With Staking Groove

## How to Order

Order this plain self-aligning bearing from our inventory online by visiting [https://military-fasteners.com/bearings/plain+self\\_aligning+bearings/MS14103-4](https://military-fasteners.com/bearings/plain+self_aligning+bearings/MS14103-4) and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.