

**Description**

single row, non-lubricated, MS14103 series bearing

\* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information****Alternate Part Numbers**[03-826-04K](#)

SKU / Model:	MS141034K
Minimum Qty (MOQ):	1
NSN:	3120-01-495-1840
Schedule B:	8482.10.5068
ECCN:	EAR99
National Motor Freight:	114820, Bearings / Bushings Noi Ball / Roller



\* See page 2 for technical characteristics

## P/N MS14103-4K Specifications

<b>Bore Diameter:</b>	0.2495 Inches Minimum And 0.2500 Inches Maximum
<b>Lubrication Material:</b>	Lubricant, Manufacturers Standard
<b>End Item Identification:</b>	Fleet Combat
<b>Outer Member Outside Diameter:</b>	0.6245 Inches Minimum And 0.6250 Inches Maximum
<b>Outer Member Width:</b>	0.3220 Inches Minimum And 0.3320 Inches Maximum
<b>Inner Member Width:</b>	0.4350 Inches Minimum And 0.4370 Inches Maximum
<b>Hardness Rating:</b>	55.0 Rockwell C Minimum Inner Member And 62.0 Rockwell C Maximum Inner Member
<b>Special Features:</b>	Letter "k" Indicates Low Breakaway Torque
<b>Material:</b>	Plastic Polytetrafluoroethylene Race Liner
<b>Material:</b>	Steel Comp 440c Inner Member
<b>Material:</b>	Steel Comp 630 Outer Race Member
<b>Material Document And Classification:</b>	Ams 5643 Assn Std Single Material Response Outer Race Member
<b>Material Document And Classification:</b>	Ams-5630 Assn Std Single Material Response Inner Member
<b>Style Designator:</b>	With Insert And/or Liner With Staking Groove

## How to Order

Order this plain self-aligning bearing from our inventory online by visiting [https://military-fasteners.com/bearings/plain+self\\_aligning+bearings/MS14103-4K](https://military-fasteners.com/bearings/plain+self_aligning+bearings/MS14103-4K) and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.