

Description

single row, non-lubricated, MS14103 series bearing

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information**Alternate Part Numbers**

[03-826-04K](#)

| | |
|-------------------------|---|
| SKU / Model: | MS141034K |
| Minimum Qty (MOQ): | 1 |
| NSN: | 3120-01-495-1840 |
| Schedule B: | 8482.10.5068 |
| ECCN: | EAR99 |
| National Motor Freight: | 114820, Bearings / Bushings Noi Ball / Roller |



* See page 2 for technical characteristics

P/N MS14103-4K Specifications

| | |
|--|---|
| Bore Diameter: | 0.2495 Inches Minimum And 0.2500 Inches Maximum |
| Lubrication Material: | Lubricant, Manufacturers Standard |
| End Item Identification: | Fleet Combat |
| Outer Member Outside Diameter: | 0.6245 Inches Minimum And 0.6250 Inches Maximum |
| Outer Member Width: | 0.3220 Inches Minimum And 0.3320 Inches Maximum |
| Inner Member Width: | 0.4350 Inches Minimum And 0.4370 Inches Maximum |
| Hardness Rating: | 55.0 Rockwell C Minimum Inner Member And 62.0 Rockwell C Maximum Inner Member |
| Special Features: | Letter "k" Indicates Low Breakaway Torque |
| Material: | Plastic Polytetrafluoroethylene Race Liner |
| Material: | Steel Comp 440c Inner Member |
| Material: | Steel Comp 630 Outer Race Member |
| Material Document And Classification: | Ams 5643 Assn Std Single Material Response Outer Race Member |
| Material Document And Classification: | Ams-5630 Assn Std Single Material Response Inner Member |
| Style Designator: | With Insert And/or Liner With Staking Groove |

How to Order

Order this plain self-aligning bearing from our inventory online by visiting https://military-fasteners.com/bearings/plain+self_aligning+bearings/MS14103-4K and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.