

Description

single row, non-lubricated, MS14103 series bearing

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information**Alternate Part Numbers**

[03-826-04K](#)

SKU / Model:	MS141034K
Minimum Qty (MOQ):	1
NSN:	3120-01-495-1840
Schedule B:	8482.10.5068
ECCN:	EAR99
National Motor Freight:	114820, Bearings / Bushings Noi Ball / Roller



* See page 2 for technical characteristics

P/N MS14103-4K Specifications

Bore Diameter:	0.2495 Inches Minimum And 0.2500 Inches Maximum
Lubrication Material:	Lubricant, Manufacturers Standard
End Item Identification:	Fleet Combat
Outer Member Outside Diameter:	0.6245 Inches Minimum And 0.6250 Inches Maximum
Outer Member Width:	0.3220 Inches Minimum And 0.3320 Inches Maximum
Inner Member Width:	0.4350 Inches Minimum And 0.4370 Inches Maximum
Hardness Rating:	55.0 Rockwell C Minimum Inner Member And 62.0 Rockwell C Maximum Inner Member
Special Features:	Letter "k" Indicates Low Breakaway Torque
Material:	Plastic Polytetrafluoroethylene Race Liner
Material:	Steel Comp 440c Inner Member
Material:	Steel Comp 630 Outer Race Member
Material Document And Classification:	Ams 5643 Assn Std Single Material Response Outer Race Member
Material Document And Classification:	Ams-5630 Assn Std Single Material Response Inner Member
Style Designator:	With Insert And/or Liner With Staking Groove

How to Order

Order this plain self-aligning bearing from our inventory online by visiting https://military-fasteners.com/bearings/plain+self_aligning+bearings/MS14103-4K and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.