

Description

inner diameter: 5/16" outer diameter: 11/16", plain, self lubricating, self aligning, low speed, wide, grooved outer ring, -65 degrees to 325 degrees

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information**Alternate Part Numbers**

[03-826-05](#)

SKU / Model:	MS141035
Minimum Qty (MOQ):	1
NSN:	3120-01-006-9150
Schedule B:	7318.15.5030
ECCN:	EAR99
National Motor Freight:	114850, Bearing / Bushing O / T Ball / Roller I / S



P/N MS14103-5 Specifications

Bore Diameter:	0.3120 Inches Minimum And 0.3125 Inches Maximum
Outer Member Outside Diameter:	0.6870 Inches Minimum And 0.6875 Inches Maximum
Outer Member Width:	0.3120 Inches Minimum And 0.3220 Inches Maximum
Inner Member Width:	0.4350 Inches Minimum And 0.4370 Inches Maximum
Static Radial Load Rating:	9400 Pounds
Hardness Rating:	23.0 Rockwell C Minimum Outer Race Member And 35.0 Rockwell C Maximum Outer Race Member
Hardness Rating:	55.0 Rockwell C Minimum Inner Member And 62.0 Rockwell C Maximum Inner Member
Material:	Plastic Polytetrafluoroethylene Race Liner
Material:	Steel Comp 440c Inner Member
Material:	Steel Comp 630 Outer Race Member
Style Designator:	With Insert And/or Liner With Staking Groove

How to Order

Order this plain self-aligning bearing from our inventory online by visiting https://military-fasteners.com/bearings/plain+self_aligning+bearings/MS14103-5 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.