

Description

inner diameter: 3/8" outer diameter: 13/16", plain, self-lubricating, self-aligning, low speed, wide, grooved outer ring,

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

Alternate Part Numbers

[03-826-06](#)

SKU / Model:	MS141036
Minimum Qty (MOQ):	1
NSN:	3120-01-016-9661
ECCN:	EAR99
National Motor Freight:	133300, Machinery / Machines Noi



* See page 2 for technical characteristics

P/N MS14103-6 Specifications

Bore Diameter:	0.3745 Inches Minimum And 0.3750 Inches Maximum
Lubrication Material:	Lubricant, Manufacturers Standard
Outer Member Outside Diameter:	0.8120 Inches Minimum And 0.8125 Inches Maximum
Outer Member Width:	0.4010 Inches Minimum And 0.4110 Inches Maximum
Inner Member Width:	0.4980 Inches Minimum And 0.5000 Inches Maximum
Static Radial Load Rating:	13700 Pounds
Hardness Rating:	23.0 Rockwell C Minimum Outer Race Member And 35.0 Rockwell C Maximum Outer Race Member
Hardness Rating:	55.0 Rockwell C Minimum Inner Member And 62.0 Rockwell C Maximum Inner Member
Lubrication Feature:	Groove External Outer Member
Material:	Plastic Polytetrafluoroethylene Race Liner
Material:	Steel Comp 440c Inner Member
Material:	Steel Comp 630 Outer Race Member
Style Designator:	With Insert And/or Liner With Staking Groove

How to Order

Order this plain self-aligning bearing from our inventory online by visiting https://military-fasteners.com/bearings/plain+self_aligning+bearings/MS14103-6 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.