

Description

inner diameter: 3/8" outer diameter: 13/16", plain, self-lubricating, self-aligning, low speed, wide, grooved outer ring,

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

Alternate Part Numbers

[03-826-06](#)

| | |
|-------------------------|----------------------------------|
| SKU / Model: | MS141036 |
| Minimum Qty (MOQ): | 1 |
| NSN: | 3120-01-016-9661 |
| ECCN: | EAR99 |
| National Motor Freight: | 133300, Machinery / Machines Noi |



P/N MS14103-6 Specifications

| | |
|---------------------------------------|---|
| Bore Diameter: | 0.3745 Inches Minimum And 0.3750 Inches Maximum |
| Lubrication Material: | Lubricant, Manufacturers Standard |
| Outer Member Outside Diameter: | 0.8120 Inches Minimum And 0.8125 Inches Maximum |
| Outer Member Width: | 0.4010 Inches Minimum And 0.4110 Inches Maximum |
| Inner Member Width: | 0.4980 Inches Minimum And 0.5000 Inches Maximum |
| Static Radial Load Rating: | 13700 Pounds |
| Hardness Rating: | 23.0 Rockwell C Minimum Outer Race Member And 35.0 Rockwell C Maximum Outer Race Member |
| Hardness Rating: | 55.0 Rockwell C Minimum Inner Member And 62.0 Rockwell C Maximum Inner Member |
| Lubrication Feature: | Groove External Outer Member |
| Material: | Plastic Polytetrafluoroethylene Race Liner |
| Material: | Steel Comp 440c Inner Member |
| Material: | Steel Comp 630 Outer Race Member |
| Style Designator: | With Insert And/or Liner With Staking Groove |

How to Order

Order this plain self-aligning bearing from our inventory online by visiting https://military-fasteners.com/bearings/plain+self_aligning+bearings/MS14103-6 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.