

Description

MS14103 series bearing

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	MS141036C
Minimum Qty (MOQ):	1
NSN:	3120-01-308-4862
Schedule B:	8482.10.5068
ECCN:	EAR99
National Motor Freight:	114820, Bearings / Bushings Noi Ball / Roller



P/N MS14103-6C Specifications

Bore Diameter:	0.3745 Inches Minimum And 0.3750 Inches Maximum
Outer Member Outside Diameter:	0.8120 Inches Minimum And 0.8125 Inches Maximum
Outer Member Width:	0.4010 Inches Minimum And 0.4110 Inches Maximum
Inner Member Width:	0.4980 Inches Minimum And 0.5000 Inches Maximum
Static Radial Load Rating:	13700 Pounds
Hardness Rating:	28.0 Rockwell C Minimum Outer Ring And 37.0 Rockwell C Maximum Outer Ring
Hardness Rating:	55.0 Rockwell C Minimum Inner Member And 62.0 Rockwell C Maximum Inner Member
Lubrication Feature:	Self-lubricating Liner Race Liner
Special Features:	Low Speed;wide Grooved Outer Ring; Neg 65 Deg To 325 Deg F
Material:	Plastic Polytetrafluoroethylene Race Liner
Material:	Steel Comp Xm-13 Inner Member
Material:	Steel Comp 630 Outer Ring
Material Document And Classification:	Ams5629h1000,ph13-8mo Assn Std Single Material Response Inner Member
Material Document And Classification:	Ams5643,17-4ph Assn Std Single Material Response Outer Ring
Surface Treatment:	Passivate Inner Member
Surface Treatment Document And Classification:	Qq-p-35,440c Fed Spec Single Treatment Response Inner Member
Style Designator:	With Insert And/or Liner With Staking Groove
Specification/standard Data:	96906-ms14103 Government Standard

How to Order

Order this plain self-aligning bearing from our inventory online by visiting https://military-fasteners.com/bearings/plain+self_aligning+bearings/MS14103-6C and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.