

Description

MS14103 series bearing

* Manufacturer certifications are shipped with your order FREE of charge


Order this part online

Additional Information

Alternate Part Numbers

[TWHT7V](#)

| | |
|-------------------------|----------------------------------|
| SKU / Model: | MS141037 |
| Minimum Qty (MOQ): | 1 |
| NSN: | 3120-01-006-9513 |
| ECCN: | EAR99 |
| National Motor Freight: | 133300, Machinery / Machines Noi |



* See page 2 for technical characteristics

P/N MS14103-7 Specifications

| | |
|---------------------------------------|---|
| Bore Diameter: | 0.4370 Inches Minimum And 0.4375 Inches Maximum |
| Outer Member Outside Diameter: | 0.9370 Inches Minimum And 0.9375 Inches Maximum |
| Outer Member Width: | 0.4370 Inches Minimum And 0.4470 Inches Maximum |
| Inner Member Width: | 0.5600 Inches Minimum And 0.5620 Inches Maximum |
| Static Radial Load Rating: | 20700 Pounds |
| Hardness Rating: | 23.0 Rockwell C Minimum Outer Race Member And 35.0 Rockwell C Maximum Outer Race Member |
| Hardness Rating: | 55.0 Rockwell C Minimum Inner Member And 62.0 Rockwell C Maximum Inner Member |
| Style Designator: | With Insert And/or Liner With Staking Groove |

How to Order

Order this plain self-aligning bearing from our inventory online by visiting https://military-fasteners.com/bearings/plain+self_aligning+bearings/MS14103-7 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.