

Description

MS14103-9P Plain Self-Aligning Bearing

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

| | |
|-------------------------|---|
| SKU / Model: | MS141039P |
| Minimum Qty (MOQ): | 1 |
| NSN: | 3120-01-338-4266 |
| ECCN: | EAR99 |
| National Motor Freight: | 114850, Bearing / Bushing O / T Ball / Roller I / S |



P/N MS14103-9P Specifications

| | |
|---|---|
| Bore Diameter: | 0.5620 Inches Minimum And 0.5625 Inches Maximum |
| Outer Member Outside Diameter: | 1.1245 Inches Minimum And 1.1250 Inches Maximum |
| Outer Member Width: | 0.5310 Inches Minimum And 0.5410 Inches Maximum |
| Inner Member Width: | 0.6850 Inches Minimum And 0.6870 Inches Maximum |
| Hardness Rating: | 43.0 Rockwell C Minimum Inner Member And 47.0 Rockwell C Maximum Inner Member 28.0 Rockwell C Minimum Outer Race Member And 37.0 Rockwell C Maximum Outer Race Member |
| Material: | Steel Comp 440c Inner Member steel Comp 630 Outer Race Member plastic Polytetrafluoroethylene Race Liner |
| Material Document And Classification: | Ams 5630 Assn Std Single Material Response Inner Member ams 5643 Assn Std Single Material Response Outer Race Member |
| Surface Treatment: | Cadmium Outer Race Member And Chromate Outer Race Member |
| Surface Treatment Document And Classification: | Qq-p-416,ty 2,cl 2 Fed Spec Single Treatment Response Outer Race Member |
| Style Designator: | With Insert And/or Liner With Staking Groove |

How to Order

Order this plain self-aligning bearing from our inventory online by visiting https://military-fasteners.com/bearings/plain+self_aligning+bearings/MS14103-9P and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.