

**Description**

Inner diameter: 1/4" outer diameter: 21/32", self lubricating, self aligning, low speed, narrow, chamfered outer ring, MS14104 series bearing

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information****Alternate Part Numbers**[ADB4](#)

SKU / Model:	MS141044
Minimum Qty (MOQ):	2
NSN:	3120-00-528-5336
Schedule B:	7318.15.5030
ECCN:	EAR99
National Motor Freight:	114850, Bearing / Bushing O / T Ball / Roller I / S



## P/N MS14104-4 Specifications

<b>Bore Diameter:</b>	0.2495 Inches Minimum And 0.2500 Inches Maximum
<b>Outer Member Outside Diameter:</b>	0.6557 Inches Minimum And 0.6562 Inches Maximum
<b>Outer Member Width:</b>	0.2450 Inches Minimum And 0.2550 Inches Maximum
<b>Inner Member Width:</b>	0.3410 Inches Minimum And 0.3430 Inches Maximum
<b>Static Radial Load Rating:</b>	6040 Pounds
<b>Hardness Rating:</b>	23.0 Rockwell C Minimum Outer Race Member And 35.0 Rockwell C Maximum Outer Race Member
<b>Hardness Rating:</b>	55.0 Rockwell C Minimum Inner Member And 62.0 Rockwell C Maximum Inner Member
<b>Material:</b>	Plastic Polytetrafluoroethylene Race Liner
<b>Material:</b>	Steel Comp 440c Inner Member
<b>Material:</b>	Steel Comp 630 Outer Race Member
<b>Style Designator:</b>	With Insert And/or Liner

## How to Order

Order this plain self-aligning bearing from our inventory online by visiting [https://military-fasteners.com/bearings/plain+self\\_aligning+bearings/MS14104-4](https://military-fasteners.com/bearings/plain+self_aligning+bearings/MS14104-4) and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.