

Description

inner diameter: 5/16" outer diameter: 3/4", plain, self-lubricating, self-aligning, low speed, narrow, chamfered outer ring, -65 f to 325 f, MS14104 series bearing

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information**Alternate Part Numbers**

[03-823-05](#)

SKU / Model:	MS141045
Minimum Qty (MOQ):	1
NSN:	3120-01-099-7316
ECCN:	EAR99
National Motor Freight:	114850, Bearing / Bushing O / T Ball / Roller I / S



P/N MS14104-5 Specifications

Bore Diameter:	0.3120 Inches Minimum And 0.3125 Inches Maximum
Outer Member Outside Diameter:	0.7495 Inches Minimum And 0.7500 Inches Maximum
Outer Member Width:	0.2760 Inches Minimum And 0.2860 Inches Maximum
Inner Member Width:	0.3730 Inches Minimum And 0.3750 Inches Maximum
Static Radial Load Rating:	8750 Pounds
Hardness Rating:	28.0 Rockwell C Minimum Outer Race Member And 37.0 Rockwell C Maximum Outer Race Member
Hardness Rating:	55.0 Rockwell C Minimum Inner Member And 62.0 Rockwell C Maximum Inner Member
Material:	Plastic Polytetrafluoroethylene Race Liner
Material:	Steel Comp 440c Inside Diameter Surface Of Body
Material:	Steel Comp 630 Outer Race Member
Surface Treatment:	Passivate Inner Member
Style Designator:	With Insert And/or Liner

How to Order

Order this plain self-aligning bearing from our inventory online by visiting https://military-fasteners.com/bearings/plain+self_aligning+bearings/MS14104-5 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.