

Description

thread: 5/8-18, self-locking, lightweight, cadmium plated, dry film lubricant

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS14144L10
Minimum Qty (MOQ):	2
NSN:	5310-01-274-9821
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



P/N MS14144L10 Specifications

Thread Class:	3b
Thread Direction:	Right-hand
Locking Feature:	Prevailing Torque All Metal Design
Washer Outside Diameter:	0.910 Inches Maximum
Lubrication:	Dry Film Lubricant
Overall Height:	0.704 Inches Minimum And 0.734 Inches Maximum
Nut Style:	Slotted Hexagon
Washer Thickness:	0.090 Inches Nominal
Width Across Flats:	0.741 Inches Minimum And 0.755 Inches Maximum
Temp Rating:	450.0 Deg Fahrenheit Nominal
Thread Series:	Unjf
Thread Quantity Per Inch:	18
Nominal Thread Size:	0.6250 Inches
Material:	Steel Overall
Surface Treatment:	Cadmium Overall And Chromate Overall
Surface Treatment Document And Classification:	Qq-p-416,type 2,class 3 Fed Spec Single Treatment Response Overall

How to Order

Order this self-locking extended washer nut from our inventory online by visiting https://military-fasteners.com/nuts/self_locking+extended+washer+nuts/MS14144L10 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.