

P/N MS14144L10

Description

thread: 5/8-18, self-locking, lightweight, cadmium plated, dry film lubricant

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model: MS14144L10

Minimum Qty (MOQ):

NSN: 5310-01-274-9821

ECCN: EAR99

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)











^{*} See page 2 for technical characteristics

P/N MS14144L10 Specifications

| Thread Class: | 3b |
|--|--|
| Thread Direction: | Right-hand |
| Locking Feature: | Prevailing Torque All Metal Design |
| Washer Outside Diameter: | 0.910 Inches Maximum |
| Lubrication: | Dry Film Lubricant |
| Overall Height: | 0.704 Inches Minimum And 0.734 Inches Maximum |
| Nut Style: | Slotted Hexagon |
| Washer Thickness: | 0.090 Inches Nominal |
| Width Across Flats: | 0.741 Inches Minimum And 0.755 Inches Maximum |
| Temp Rating: | 450.0 Deg Fahrenheit Nominal |
| Thread Series: | Unjf |
| Thread Quantity Per Inch: | 18 |
| Nominal Thread Size: | 0.6250 Inches |
| Material: | Steel Overall |
| Surface Treatment: | Cadmium Overall And Chromate Overall |
| Surface Treatment Document And Classification: | Qq-p-416,type 2,class 3 Fed Spec Single Treatment Response Overall |

How to Order

Order this self-locking extended washer nut from our inventory online by visiting https://military-fasteners.com/nuts/self_locking+extended+washer+nuts/MS14144L10 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-nuts/self_locking+extended+washer+nuts/MS14144L10 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-nuts/self_locking+extended+washer+nuts/MS14144L10 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-nuts/self_locking+extended+washer+nuts/ms14144L10 and selecting the quantity you want then click "add to cart".