

P/N MS14144L3

Description

Thread: 10-32, castellated, self locking, lightweight, cadmium plated, dry film lubricant, MS14144 series nut

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

Alternate Part Numbers

PHCR353M

SKU / Model: MS14144L3

Minimum Qty (MOQ): 10

NSN: 5310-01-057-3110

Schedule B: 7318.16.0000

ECCN: EAR99

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)









P/N MS14144L3 Specifications

| Thread Class: | 3b |
|--|---|
| Thread Direction: | Right-hand |
| Locking Feature: | Prevailing Torque All Metal Design |
| Washer Outside Diameter: | 0.325 Inches Maximum |
| Lubrication: | Dry Film Lubricant |
| Overall Height: | 0.235 Inches Minimum And 0.265 Inches Maximum |
| Nut Style: | Slotted Hexagon |
| Washer Thickness: | 0.025 Inches Nominal |
| Width Across Flats: | 0.243 Inches Minimum And 0.252 Inches Maximum |
| Temp Rating: | 450.0 Deg Fahrenheit Maximum |
| Thread Series: | Unjf |
| Thread Quantity Per Inch: | 32 |
| Nominal Thread Size: | 0.190 Inches |
| Bearing Surface Finish: | 125.0 Microinches |
| Material: | Steel Overall |
| Surface Treatment: | Cadmium Overall |
| Surface Treatment Document And Classification: | Qq-p-416 Fed Spec Single Treatment Response Overall |

How to Order

Order this self-locking extended washer nut from our inventory online by visiting https://military-fasteners.com/nuts/self_locking+extended+washer+nuts/MS14144L3 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out here to complete your order.