

**Description**

thread: 5/16-24, self locking, lightweight, cadmium plated, dry film lubricant, MS14144 series nut

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	MS14144L5
Minimum Qty (MOQ):	10
NSN:	5310-00-090-4136
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



## P/N MS14144L5 Specifications

<b>Thread Class:</b>	3b
<b>Thread Direction:</b>	Right-hand
<b>Locking Feature:</b>	Prevailing Torque All Metal Design
<b>Washer Outside Diameter:</b>	0.520 Inches Maximum
<b>Lubrication:</b>	Dry Film Lubricant
<b>Overall Height:</b>	0.328 Inches Nominal
<b>Nut Style:</b>	Hexagon
<b>Washer Thickness:</b>	0.055 Inches Nominal
<b>Width Across Flats:</b>	0.367 Inches Minimum And 0.378 Inches Maximum
<b>Temp Rating:</b>	450.0 Deg Fahrenheit Nominal
<b>Thread Series:</b>	Unjf
<b>Thread Quantity Per Inch:</b>	24
<b>Nominal Thread Size:</b>	0.312 Inches
<b>Material:</b>	Steel Overall
<b>Surface Treatment:</b>	Cadmium Overall
<b>Surface Treatment Document And Classification:</b>	Qq-p-416,ty 2,cl 3 Fed Spec Single Treatment Response Overall

## How to Order

Order this self-locking extended washer nut from our inventory online by visiting [https://military-fasteners.com/nuts/self\\_locking+extended+washer+nuts/MS14144L5](https://military-fasteners.com/nuts/self_locking+extended+washer+nuts/MS14144L5) and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.