

Description

thread: 5/8-18, self-locking nut - lightweight - thin cadmium plated, dry film lubricant, 450°, f

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|---|
| SKU / Model: | MS14145L10 |
| Minimum Qty (MOQ): | 1 |
| NSN: | 5310-01-058-3982 |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |

NO IMAGE
AVAILABLE

P/N MS14145L10 Specifications

| | |
|---|---|
| Thread Class: | 3b |
| Thread Direction: | Right-hand |
| Locking Feature: | Prevailing Torque All Metal Design |
| Washer Outside Diameter: | 0.910 Inches Maximum |
| Lubrication: | Dry Film Lubricant |
| Overall Height: | 0.298 Inches Minimum And 0.328 Inches Maximum |
| Nut Style: | Slotted Hexagon |
| Washer Thickness: | 0.055 Inches Nominal |
| Width Across Flats: | 0.741 Inches Minimum And 0.755 Inches Maximum |
| Temp Rating: | 450.0 Deg Fahrenheit Maximum |
| Thread Series: | Unjf |
| Thread Quantity Per Inch: | 18 |
| Nominal Thread Size: | 0.625 Inches |
| Bearing Surface Finish: | 125.0 Microinches |
| Material: | Steel Overall |
| Surface Treatment: | Cadmium Overall |
| Surface Treatment Document And Classification: | Qq-p-416 Fed Spec Single Treatment Response Overall |

How to Order

Order this self-locking extended washer nut from our inventory online by visiting https://military-fasteners.com/nuts/self_locking+extended+washer+nuts/MS14145L10 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.