

P/N MS14145L5

Description

Thread: 5/16-24, self-locking nut, lightweight, thin cadmium plated, dry film lubricant, MS14145 series nut

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

Alternate Part Numbers

NSA5059-5

SKU / Model: MS14145L5

Minimum Qty (MOQ): 10

NSN: 5310-01-055-3854

Schedule B: 7318.16.0085

ECCN: EAR99

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)









^{*} See page 2 for technical characteristics

P/N MS14145L5 Specifications

Thread Class:	3b
Thread Direction:	Right-hand
Locking Feature:	Prevailing Torque All Metal Design
Washer Outside Diameter:	0.520 Inches Maximum
Lubrication:	Dry Film Lubricant
Overall Height:	0.173 Inches Minimum And 0.203 Inches Maximum
Nut Style:	Slotted Hexagon
Washer Thickness:	0.020 Inches Nominal
Width Across Flats:	0.367 Inches Minimum And 0.378 Inches Maximum
Temp Rating:	450.0 Deg Fahrenheit Maximum
Thread Series:	Unjf
Thread Quantity Per Inch:	24
Nominal Thread Size:	0.312 Inches
Bearing Surface Finish:	125.0 Microinches
Material:	Steel Overall
Surface Treatment:	Cadmium Overall
Surface Treatment Document And Classification:	Qq-p-416 Fed Spec Single Treatment Response Overall

How to Order

Order this self-locking extended washer nut from our inventory online by visiting https://military-fasteners.com/nuts/self_locking+extended+washer+nuts/MS14145L5 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out here to complete your order.