

P/N MS14145L6

Description

thread: 3/8-24, self-locking nut, lightweight, thin cadmium plated, dry film lubricant, MS14145 series nut

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model: MS14145L6

Minimum Qty (MOQ): 5

NSN: 5310-01-055-3853

ECCN: EAR99

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)









P/N MS14145L6 Specifications

| Thread Class: | 3b |
|--|---|
| Thread Direction: | Right-hand |
| Locking Feature: | Prevailing Torque All Metal Design |
| Washer Outside Diameter: | 0.579 Inches Maximum |
| Lubrication: | Dry Film Lubricant |
| Overall Height: | 0.204 Inches Minimum And 0.234 Inches Maximum |
| Nut Style: | Slotted Hexagon |
| Washer Thickness: | 0.025 Inches Nominal |
| Width Across Flats: | 0.429 Inches Minimum And 0.440 Inches Maximum |
| Temp Rating: | 450.0 Deg Fahrenheit Maximum |
| Thread Series: | Unjf |
| Thread Quantity Per Inch: | 24 |
| Nominal Thread Size: | 0.375 Inches |
| Bearing Surface Finish: | 125.0 Microinches |
| Material: | Steel Overall |
| Surface Treatment: | Cadmium Overall |
| Surface Treatment Document And Classification: | Qq-p-416 Fed Spec Single Treatment Response Overall |

How to Order

Order this self-locking extended washer nut from our inventory online by visiting https://military-fasteners.com/nuts/self_locking+extended+washer+nuts/MS14145L6 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out here to complete your order.