

Description

thread: 7/16-20, self-locking nut, lightweight, thin cadmium plated, dry film lubricant

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|---|
| SKU / Model: | MS14145L7 |
| Minimum Qty (MOQ): | 5 |
| NSN: | 5310-01-059-7517 |
| ECCN: | EAR99 |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |



P/N MS14145L7 Specifications

| | |
|---|---|
| Thread Class: | 3b |
| Thread Direction: | Right-hand |
| Locking Feature: | Prevailing Torque All Metal Design |
| Washer Outside Diameter: | 0.645 Inches Maximum |
| Lubrication: | Dry Film Lubricant |
| Overall Height: | 0.204 Inches Minimum And 0.234 Inches Maximum |
| Nut Style: | Slotted Hexagon |
| Washer Thickness: | 0.025 Inches Nominal |
| Width Across Flats: | 0.492 Inches Minimum And 0.504 Inches Maximum |
| Temp Rating: | 450.0 Deg Fahrenheit Maximum |
| Thread Series: | Unjf |
| Thread Quantity Per Inch: | 20 |
| Nominal Thread Size: | 0.438 Inches |
| Material: | Steel Overall |
| Surface Treatment: | Cadmium Overall |
| Surface Treatment Document And Classification: | Qq-p-416 Fed Spec Single Treatment Response Overall |

How to Order

Order this self-locking extended washer nut from our inventory online by visiting https://military-fasteners.com/nuts/self_locking+extended+washer+nuts/MS14145L7 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.