

**Description**

Hole Diameter: 5/8

\* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	MS1415510
Minimum Qty (MOQ):	10
NSN:	5310-01-092-1257
ECCN:	EAR99
National Motor Freight:	194160, Washer Or Gaskets, Iron Or Steel,



NO IMAGE  
AVAILABLE

## P/N MS14155-10 Specifications

<b>Hole Diameter:</b>	0.627 Inches Minimum And 0.631 Inches Maximum
<b>Outside Diameter:</b>	1.256 Inches Minimum And 1.266 Inches Maximum
<b>Material Thickness:</b>	0.212 Inches Minimum And 0.226 Inches Maximum
<b>Hardness Rating:</b>	38.0 Rockwell C Minimum And 43.0 Rockwell C Maximum
<b>Top Recess Diameter:</b>	0.775 Inches Minimum And 0.785 Inches Maximum
<b>Bottom Recess Angle:</b>	90.0 Degrees Nominal
<b>Top Recess Angle:</b>	90.0 Degrees Nominal
<b>Bottom Recess Diameter:</b>	0.775 Inches Minimum And 0.785 Inches Maximum
<b>Material:</b>	Steel Comp 4130 Overall
<b>Material Document And Classification:</b>	Mil-s-6758 Mil Spec Single Material Response Overall Or Mil-s-18729 Mil Spec Single Material Response Overall
<b>Surface Treatment:</b>	Cadmium Overall
<b>Surface Treatment Document And Classification:</b>	Qq-p-416,ty 2,c1 2 Fed Spec Single Treatment Response Overall
<b>Style Designator:</b>	Recessed Both Sides

## How to Order

Order this washer from our inventory online by visiting <https://military-fasteners.com/washers/recessed+washers/MS14155-10> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.