

Description

Hole Diameter: 5/8

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	MS1415510
Minimum Qty (MOQ):	10
NSN:	5310-01-092-1257
ECCN:	EAR99
National Motor Freight:	194160, Washer Or Gaskets, Iron Or Steel,



NO IMAGE
AVAILABLE

P/N MS14155-10 Specifications

Hole Diameter:	0.627 Inches Minimum And 0.631 Inches Maximum
Outside Diameter:	1.256 Inches Minimum And 1.266 Inches Maximum
Material Thickness:	0.212 Inches Minimum And 0.226 Inches Maximum
Hardness Rating:	38.0 Rockwell C Minimum And 43.0 Rockwell C Maximum
Top Recess Diameter:	0.775 Inches Minimum And 0.785 Inches Maximum
Bottom Recess Angle:	90.0 Degrees Nominal
Top Recess Angle:	90.0 Degrees Nominal
Bottom Recess Diameter:	0.775 Inches Minimum And 0.785 Inches Maximum
Material:	Steel Comp 4130 Overall
Material Document And Classification:	Mil-s-6758 Mil Spec Single Material Response Overall Or Mil-s-18729 Mil Spec Single Material Response Overall
Surface Treatment:	Cadmium Overall
Surface Treatment Document And Classification:	Qq-p-416,ty 2,c1 2 Fed Spec Single Treatment Response Overall
Style Designator:	Recessed Both Sides

How to Order

Order this washer from our inventory online by visiting <https://military-fasteners.com/washers/recessed+washers/MS14155-10> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.