

Description

Hole Diameter: 5/8

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

| | |
|-------------------------|---|
| SKU / Model: | MS1415510 |
| Minimum Qty (MOQ): | 10 |
| NSN: | 5310-01-092-1257 |
| ECCN: | EAR99 |
| National Motor Freight: | 194160, Washer Or Gaskets, Iron Or Steel, |

NO IMAGE
AVAILABLE

P/N MS14155-10 Specifications

| | |
|---|---|
| Hole Diameter: | 0.627 Inches Minimum And 0.631 Inches Maximum |
| Outside Diameter: | 1.256 Inches Minimum And 1.266 Inches Maximum |
| Material Thickness: | 0.212 Inches Minimum And 0.226 Inches Maximum |
| Hardness Rating: | 38.0 Rockwell C Minimum And 43.0 Rockwell C Maximum |
| Top Recess Diameter: | 0.775 Inches Minimum And 0.785 Inches Maximum |
| Bottom Recess Angle: | 90.0 Degrees Nominal |
| Top Recess Angle: | 90.0 Degrees Nominal |
| Bottom Recess Diameter: | 0.775 Inches Minimum And 0.785 Inches Maximum |
| Material: | Steel Comp 4130 Overall |
| Material Document And Classification: | Mil-s-6758 Mil Spec Single Material Response Overall Or Mil-s-18729 Mil Spec Single Material Response Overall |
| Surface Treatment: | Cadmium Overall |
| Surface Treatment Document And Classification: | Qq-p-416,ty 2,c1 2 Fed Spec Single Treatment Response Overall |
| Style Designator: | Recessed Both Sides |

How to Order

Order this washer from our inventory online by visiting <https://military-fasteners.com/washers/recessed+washers/MS14155-10> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.