

Description

Hole Diameter: 3/8

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

| | |
|-------------------------|---|
| SKU / Model: | MS141556 |
| Minimum Qty (MOQ): | 10 |
| NSN: | 5310-01-089-5672 |
| ECCN: | EAR99 |
| National Motor Freight: | 194160, Washer Or Gaskets, Iron Or Steel, |



NO IMAGE
AVAILABLE

P/N MS14155-6 Specifications

| | |
|---|---|
| Hole Diameter: | 0.376 Inches Minimum And 0.380 Inches Maximum |
| Outside Diameter: | 0.756 Inches Minimum And 0.766 Inches Maximum |
| Material Thickness: | 0.144 Inches Minimum And 0.158 Inches Maximum |
| Hardness Rating: | 39.0 Rockwell C Minimum And 43.0 Rockwell C Maximum |
| Top Recess Diameter: | 0.494 Inches Minimum And 0.504 Inches Maximum |
| Bottom Recess Angle: | 90.0 Degrees Nominal |
| Top Recess Angle: | 90.0 Degrees Nominal |
| Bottom Recess Diameter: | 0.494 Inches Minimum And 0.504 Inches Maximum |
| Material: | Steel Comp 4130 Overall |
| Material Document And Classification: | Mil-s-5059,ty 302,1/2 Hard Mil Spec 1st Material Response Overall Or Mil-s-18729 Mil Spec 2nd Material Response Overall |
| Surface Treatment: | Cadmium Overall |
| Surface Treatment Document And Classification: | Qq-p-416,ty 2,cl 2 Fed Spec Single Treatment Response Overall |
| Style Designator: | Recessed Both Sides |

How to Order

Order this recessed washer from our inventory online by visiting <https://military-fasteners.com/washers/recessed+washers/MS14155-6> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.