

**Description**

Size: 7/16, countersunk, MS14155 series washer

\* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	MS141557
Minimum Qty (MOQ):	10
NSN:	5310-01-066-1695
Schedule B:	7318.22.0000
ECCN:	EAR99
National Motor Freight:	194160, Washer Or Gaskets, Iron Or Steel,



\* See page 2 for technical characteristics

## P/N MS14155-7 Specifications

<b>Hole Diameter:</b>	0.439 Inches Minimum And 0.443 Inches Maximum
<b>Outside Diameter:</b>	0.868 Inches Minimum And 0.878 Inches Maximum
<b>Material Thickness:</b>	0.144 Inches Minimum And 0.158 Inches Maximum
<b>Hardness Rating:</b>	39.0 Rockwell C Minimum And 43.0 Rockwell C Maximum
<b>Top Recess Diameter:</b>	0.556 Inches Minimum And 0.566 Inches Maximum
<b>Bottom Recess Angle:</b>	90.0 Degrees Nominal
<b>Top Recess Angle:</b>	90.0 Degrees Nominal
<b>Bottom Recess Diameter:</b>	0.556 Inches Minimum And 0.566 Inches Maximum
<b>Material:</b>	Steel Comp 4130 Overall
<b>Material Document And Classification:</b>	Mil-s-5059,ty 302,1/2 Hard Mil Spec 1st Material Response Overall Or Mil-s-18729 Mil Spec 2nd Material Response Overall
<b>Surface Treatment:</b>	Cadmium Overall And Chromate Overall
<b>Surface Treatment Document And Classification:</b>	Qq-p-416,ty 2,cl 2 Fed Spec Single Treatment Response Overall
<b>Style Designator:</b>	Recessed Both Sides

## How to Order

Order this recessed washer from our inventory online by visiting <https://military-fasteners.com/washers/recessed+washers/MS14155-7> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.