

P/N MS14181-04014L

Description

Fastener Length: 1-25/64", Thread: 1/4-28, Thread Length: 1/2

* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

Order this part online

Additional Information

SKU / Model:	MS1418104014L
Minimum Qty (MOQ):	5
NSN:	5306-01-474-1095
Schedule B:	7508.90.5000
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



^{*} See page 2 for technical characteristics

P/N MS14181-04014L Specifications

Thread Direction: Right-hand Thread Length: 0.495 Inches Minimum Fastener Length: 1.380 Inches Minimum And 1.410 Inches Maximum Head Style: Spline Extended Washer Head Height: 0.240 Inches Minimum And 0.260 Inches Maximum Extended Washer Diameter: 0.460 Inches Minimum And 0.470 Inches Maximum Extended Washer Thickness: 0.026 Inches Minimum And 0.046 Inches Maximum Grip Diameter: 0.2485 Inches Minimum And 0.2495 Inches Maximum Head Minor Diameter: 0.235 Inches Minimum And 0.250 Inches Maximum End Item Identification: F/a-18e Aircraft Nominal Thread Diameter: 0.250 Inches Grip Length: 0.865 Inches Minimum And 0.885 Inches Maximum Thread Quantity Per Inch: 28 Minimum Tensile Strength: 220000 Pounds Per Square Inch		
Thread Length: 0.495 Inches Minimum Fastener Length: 1.380 Inches Minimum And 1.410 Inches Maximum Head Style: Spline Extended Washer Head Height: 0.240 Inches Minimum And 0.260 Inches Maximum Extended Washer Diameter: 0.460 Inches Minimum And 0.470 Inches Maximum Extended Washer Thickness: 0.026 Inches Minimum And 0.046 Inches Maximum Grip Diameter: 0.2485 Inches Minimum And 0.2495 Inches Maximum Head Minor Diameter: 0.235 Inches Minimum And 0.250 Inches Maximum End Item Identification: F/a-18e Aircraft Nominal Thread Diameter: 0.250 Inches Grip Length: 0.865 Inches Minimum And 0.885 Inches Maximum Thread Quantity Per Inch: 28	Thread Class:	3a
Fastener Length: 1.380 Inches Minimum And 1.410 Inches Maximum Head Style: Spline Extended Washer Head Height: 0.240 Inches Minimum And 0.260 Inches Maximum Extended Washer Diameter: 0.460 Inches Minimum And 0.470 Inches Maximum Extended Washer Thickness: 0.026 Inches Minimum And 0.046 Inches Maximum Grip Diameter: 0.2485 Inches Minimum And 0.2495 Inches Maximum Head Minor Diameter: 0.235 Inches Minimum And 0.250 Inches Maximum End Item Identification: F/a-18e Aircraft Nominal Thread Diameter: 0.250 Inches Grip Length: 0.865 Inches Minimum And 0.885 Inches Maximum Thread Quantity Per Inch: 28	Thread Direction:	Right-hand
Head Style: Head Height: 0.240 Inches Minimum And 0.260 Inches Maximum Extended Washer Diameter: 0.460 Inches Minimum And 0.470 Inches Maximum Extended Washer Thickness: 0.026 Inches Minimum And 0.046 Inches Maximum Grip Diameter: 0.2485 Inches Minimum And 0.2495 Inches Maximum Head Minor Diameter: 0.235 Inches Minimum And 0.250 Inches Maximum End Item Identification: F/a-18e Aircraft Nominal Thread Diameter: 0.250 Inches Grip Length: 0.865 Inches Minimum And 0.885 Inches Maximum Thread Quantity Per Inch: 28	Thread Length:	0.495 Inches Minimum
Head Height: 0.240 Inches Minimum And 0.260 Inches Maximum Extended Washer Diameter: 0.460 Inches Minimum And 0.470 Inches Maximum Extended Washer Thickness: 0.026 Inches Minimum And 0.046 Inches Maximum Grip Diameter: 0.2485 Inches Minimum And 0.2495 Inches Maximum Head Minor Diameter: 0.235 Inches Minimum And 0.250 Inches Maximum End Item Identification: F/a-18e Aircraft Nominal Thread Diameter: 0.250 Inches Grip Length: 0.865 Inches Minimum And 0.885 Inches Maximum Thread Quantity Per Inch: 28	Fastener Length:	1.380 Inches Minimum And 1.410 Inches Maximum
Extended Washer Diameter: Extended Washer Thickness: 0.026 Inches Minimum And 0.046 Inches Maximum Grip Diameter: 0.2485 Inches Minimum And 0.2495 Inches Maximum Head Minor Diameter: 0.235 Inches Minimum And 0.250 Inches Maximum End Item Identification: F/a-18e Aircraft Nominal Thread Diameter: 0.250 Inches Grip Length: 0.865 Inches Minimum And 0.885 Inches Maximum Thread Quantity Per Inch: 28	Head Style:	Spline Extended Washer
Extended Washer Thickness: 0.026 Inches Minimum And 0.046 Inches Maximum 0.2485 Inches Minimum And 0.2495 Inches Maximum Head Minor Diameter: 0.235 Inches Minimum And 0.250 Inches Maximum End Item Identification: F/a-18e Aircraft Nominal Thread Diameter: 0.250 Inches Grip Length: 0.865 Inches Minimum And 0.885 Inches Maximum Thread Quantity Per Inch: 28	Head Height:	0.240 Inches Minimum And 0.260 Inches Maximum
Grip Diameter: 0.2485 Inches Minimum And 0.2495 Inches Maximum Head Minor Diameter: 0.235 Inches Minimum And 0.250 Inches Maximum End Item Identification: F/a-18e Aircraft Nominal Thread Diameter: 0.250 Inches Grip Length: 0.865 Inches Minimum And 0.885 Inches Maximum Thread Quantity Per Inch: 28	Extended Washer Diameter:	0.460 Inches Minimum And 0.470 Inches Maximum
Head Minor Diameter:0.235 Inches Minimum And 0.250 Inches MaximumEnd Item Identification:F/a-18e AircraftNominal Thread Diameter:0.250 InchesGrip Length:0.865 Inches Minimum And 0.885 Inches MaximumThread Quantity Per Inch:28	Extended Washer Thickness:	0.026 Inches Minimum And 0.046 Inches Maximum
End Item Identification: F/a-18e Aircraft Nominal Thread Diameter: 0.250 Inches Grip Length: 0.865 Inches Minimum And 0.885 Inches Maximum Thread Quantity Per Inch: 28	Grip Diameter:	0.2485 Inches Minimum And 0.2495 Inches Maximum
Nominal Thread Diameter: 0.250 Inches Grip Length: 0.865 Inches Minimum And 0.885 Inches Maximum Thread Quantity Per Inch: 28	Head Minor Diameter:	0.235 Inches Minimum And 0.250 Inches Maximum
Grip Length: 0.865 Inches Minimum And 0.885 Inches Maximum Thread Quantity Per Inch: 28	End Item Identification:	F/a-18e Aircraft
Thread Quantity Per Inch: 28	Nominal Thread Diameter:	0.250 Inches
	Grip Length:	0.865 Inches Minimum And 0.885 Inches Maximum
Minimum Tensile Strength: 220000 Pounds Per Square Inch	Thread Quantity Per Inch:	28
	Minimum Tensile Strength:	220000 Pounds Per Square Inch
Criticality Code Justification: Agav	Criticality Code Justification:	Agav
Surface Finish: 32.0 Microinches Bearing Surface Of Head	Surface Finish:	32.0 Microinches Bearing Surface Of Head
Material: Nickel Alloy 718 Overall	Material:	Nickel Alloy 718 Overall
Material Document And Classification: Ams 5662 Assn Std Single Material Response Overall Or Ams 5663 Assn Std Single Material Response Overall	Material Document And Classification:	Ams 5662 Assn Std Single Material Response Overall Or Ams 5663 Assn Std Single Material Response Overall
Surface Treatment: Passivate Overall	Surface Treatment:	Passivate Overall
Thread Series Designator: Unjf	Thread Series Designator:	Unjf

How to Order

Order this machien bolt from our inventory online by visiting https://military-fasteners.com/bolts/machine+bolts/MS14181-04014L and selecting the quantity you want then click "add to cart". Once items are in your cart you can check outhere to complete your order.