

Description

MS14181 series bolt

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	MS1418106028P
Minimum Qty (MOQ):	1
NSN:	5306-01-477-6718
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



* See page 2 for technical characteristics

P/N MS14181-06028P Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.659 Inches Minimum
Fastener Length:	2.419 Inches Minimum And 2.449 Inches Maximum
Head Style:	Spline Extended Washer
Head Height:	0.327 Inches Minimum And 0.347 Inches Maximum
Extended Washer Diameter:	0.691 Inches Minimum And 0.701 Inches Maximum
Extended Washer Thickness:	0.044 Inches Minimum And 0.064 Inches Maximum
Grip Diameter:	0.3735 Inches Minimum And 0.3745 Inches Maximum
Head Minor Diameter:	0.423 Inches Minimum And 0.438 Inches Maximum
Nominal Thread Diameter:	0.375 Inches
Grip Length:	1.740 Inches Minimum And 1.760 Inches Maximum
Thread Quantity Per Inch:	24
Minimum Tensile Strength:	220000 Pounds Per Square Inch
Material:	Nickel Alloy 718 Overall
Material Document And Classification:	Ams5662 Assn Std Single Material Response Overall Or 5663 Assn Std Single Material Response Overall
Surface Treatment:	Cadmium Overall
Surface Treatment Document And Classification:	Qq-p-416,type li,class 2 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unjf

How to Order

Order this shear bolt from our inventory online by visiting <https://military-fasteners.com/bolts/shear+bolts/MS14181-06028P> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.