

Description

Thread Size: 3/4"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|---|
| SKU / Model: | MS14182L12 |
| Minimum Qty (MOQ): | 1 EA |
| NSN: | 5310-01-499-3270 |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |

NO IMAGE
AVAILABLE

* See page 2 for technical characteristics

P/N MS14182L12 Specifications

| | |
|--|--|
| Thread Class: | 3b |
| Thread Direction: | Right-hand |
| Locking Feature: | Prevailing Torque All Metal Design |
| Washer Outside Diameter: | 1.296 Inches Maximum |
| Lubrication: | Dry Film Lubricant |
| Overall Height: | 0.860 Inches Maximum |
| Nut Style: | Spline Drive |
| Drive Point Quantity: | 12 |
| Washer Thickness: | 0.090 Inches Minimum |
| End Item Identification: | Used On F-22 Aircraft |
| Temp Rating: | 450.0 Deg Fahrenheit Maximum |
| Thread Series: | Unjf |
| Thread Quantity Per Inch: | 16 |
| Nominal Thread Size: | 0.750 Inches |
| Material: | Nickel Alloy 718 Overall |
| Material Document And Classification: | Ams5662 Assn Std Single Material Response Overall Or Ams5663 Assn Std Single Material Response Overall |

How to Order

Order this nut from our inventory online by visiting https://military-fasteners.com/nuts/self_locking+extended+washer+nuts/MS14182L12 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.