

**Description**

Hole Diameter: 1/4"

\* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	MS14183C3
Minimum Qty (MOQ):	20 EA
NSN:	5310-01-305-2588
National Motor Freight:	139820, Nickel Bolts / Nails / Nuts / Rivets Etc

NO IMAGE  
AVAILABLE

## P/N MS14183-C3 Specifications

<b>Hole Diameter:</b>	0.191 Inches Minimum And 0.195 Inches Maximum
<b>Outside Diameter:</b>	0.362 Inches Minimum And 0.372 Inches Maximum
<b>Recess Diameter:</b>	0.238 Inches Minimum And 0.248 Inches Maximum
<b>Material Thickness:</b>	0.057 Inches Minimum And 0.069 Inches Maximum
<b>Hardness Rating:</b>	36.0 Rockwell C Minimum And 45.0 Rockwell C Maximum
<b>Recess Angle:</b>	90.0 Degrees Nominal
<b>Material:</b>	Nickel Alloy 718 Overall
<b>Material Document And Classification:</b>	Ams 5596 Assn Std Single Material Response Overall And Ams 5597 Assn Std Single Material Response Overall And Ams 5662 Assn Std Single Material Response Overall
<b>Style Designator:</b>	15 Recessed

## How to Order

Order this washer from our inventory online by visiting [https://military-fasteners.com/nuts/self\\_locking+extended+washer+nuts/MS14183-C3](https://military-fasteners.com/nuts/self_locking+extended+washer+nuts/MS14183-C3) and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.