

**Description**

Hole Diameter: 5/16",

\* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information****Alternate Part Numbers**[MS14183-C5](#)

SKU / Model:	MS14183C5
Minimum Qty (MOQ):	10
NSN:	5310-01-304-8736
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



## P/N MS14183C5 Specifications

<b>Hole Diameter:</b>	0.314 Inches Minimum And 0.318 Inches Maximum
<b>Outside Diameter:</b>	0.575 Inches Minimum And 0.585 Inches Maximum
<b>Recess Diameter:</b>	0.386 Inches Minimum And 0.396 Inches Maximum
<b>Material Thickness:</b>	0.057 Inches Minimum And 0.069 Inches Maximum
<b>Hardness Rating:</b>	36.0 Rockwell C Minimum And 45.0 Rockwell C Maximum
<b>Recess Angle:</b>	90.0 Degrees Nominal
<b>Material:</b>	Nickel Alloy 718 Overall
<b>Material Document And Classification:</b>	Ams 5596 Assn Std Single Material Response Overall Or Ams 5597 Assn Std Single Material Response Overall Or Ams 5662 Assn Std Single Material Response Overall
<b>Style Designator:</b>	15 Recessed

## How to Order

Order this recessed washer from our inventory online by visiting <https://military-fasteners.com/washers/recessed+washers/MS14183C5> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.