

Description

Hole Diameter: 1/2", MS14183 series washer

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information**Alternate Part Numbers**[MS14183-C8](#)

| | |
|-------------------------|---|
| SKU / Model: | MS14183C8 |
| Minimum Qty (MOQ): | 2 |
| NSN: | 5310-01-306-7880 |
| ECCN: | EAR99 |
| National Motor Freight: | 194160, Washer Or Gaskets, Iron Or Steel, |

NO IMAGE
AVAILABLE

P/N MS14183C8 Specifications

| | |
|--|--|
| Hole Diameter: | 0.501 Inches Minimum And 0.505 Inches Maximum |
| Outside Diameter: | 0.922 Inches Minimum And 0.932 Inches Maximum |
| Recess Diameter: | 0.614 Inches Minimum And 0.624 Inches Maximum |
| Material Thickness: | 0.071 Inches Minimum And 0.085 Inches Maximum |
| Hardness Rating: | 36.0 Rockwell C Minimum And 45.0 Rockwell C Maximum |
| Recess Angle: | 90.0 Degrees Nominal |
| Material: | Nickel Alloy 718 Overall |
| Material Document And Classification: | Ams 5596 Assn Std Single Material Response Overall Or Ams 5597 Assn Std Single Material Response Overall Or Ams 5662 Assn Std Single Material Response Overall |
| Style Designator: | 15 Recessed |

How to Order

Order this flat washer from our inventory online by visiting <https://military-fasteners.com/washers/flat+washers/MS14183C8> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.