

Description

Hole Diameter: 5/8

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS14183C9
Minimum Qty (MOQ):	2
NSN:	5310-01-304-8737
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



* See page 2 for technical characteristics

P/N MS14183C9 Specifications

Hole Diameter:	0.564 Inches Minimum And 0.568 Inches Maximum
Outside Diameter:	1.037 Inches Minimum And 1.047 Inches Maximum
Recess Diameter:	0.688 Inches Minimum And 0.698 Inches Maximum
Material Thickness:	0.071 Inches Minimum And 0.085 Inches Maximum
Hardness Rating:	36.0 Rockwell C Minimum And 45.0 Rockwell C Maximum
Recess Angle:	90.0 Degrees Nominal
Material:	Nickel Alloy 718 Overall
Material Document And Classification:	Ams 5596 Assn Std Single Material Response Overall Or Ams 5597 Assn Std Single Material Response Overall Or Ams 5662 Assn Std Single Material Response Overall
Style Designator:	15 Recessed

How to Order

Order this recessed washer from our inventory online by visiting <https://military-fasteners.com/washers/recessed+washers/MS14183C9> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.