

**Description**

Hole Diameter: 3/4", Diameter: 1-3/8", Thickness: 1/8

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

|                    |                  |
|--------------------|------------------|
| SKU / Model:       | MS14183L12       |
| Minimum Qty (MOQ): | 1                |
| NSN:               | 5310-01-494-2806 |
| ECCN:              | EAR99            |



\* See page 2 for technical characteristics

## P/N MS14183L-12 Specifications

|  |   |
|--|---|
| <b>Cross-sectional Shape Style:</b>          | Rectangular   |
| <b>Hole Diameter:</b>                        | 0.789 Inches Minimum And 0.793 Inches Maximum   |
| <b>Peripheral Shape Style:</b>               | Round   |
| <b>Center Hole Shape Style:</b>              | 1 Round   |
| <b>Thickness:</b>                            | 0.099 Inches Minimum And 0.119 Inches Maximum   |
| <b>Overall Diameter:</b>                     | 1.384 Inches Minimum And 1.394 Inches Maximum   |
| <b>End Item Identification:</b>              | Used On F-22 Aircraft   |
| <b>Hardness Rating:</b>                      | 36.0 Rockwell C Minimum And 45.0 Rockwell C Maximum   |
| <b>Material:</b>                             | Nickel Alloy 718 Overall  |
| <b>Material Document And Classification:</b> | Ams 5596 Assn Std 1st Material Response Overall Or Ams 5597 Assn Std 2nd Material Response Overall Or Ams 5662, Nickel Alloy 718 Assn Std 3rd Material Response Overall |
| <b>Surface Treatment:</b>                    | Passivate Overall   |

## How to Order

Order this washer from our inventory online by visiting <https://military-fasteners.com/washers/flat+washers/MS14183L-12> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.