

P/N MS14183L-12

Description

Hole Diameter: 3/4", Diameter: 1-3/8", Thickness: 1/8

* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

Order this part online

Additional Information

SKU / Model:	MS14183L12
Minimum Qty (MOQ):	1
NSN:	5310-01-494-2806
ECCN:	EAR99



^{*} See page 2 for technical characteristics

P/N MS14183L-12 Specifications

Cross-sectional Shape Style:	Rectangular
Hole Diameter:	0.789 Inches Minimum And 0.793 Inches Maximum
Peripheral Shape Style:	Round
Center Hole Shape Style:	1 Round
Thickness:	0.099 Inches Minimum And 0.119 Inches Maximum
Overall Diameter:	1.384 Inches Minimum And 1.394 Inches Maximum
End Item Identification:	Used On F-22 Aircraft
Hardness Rating:	36.0 Rockwell C Minimum And 45.0 Rockwell C Maximum
Material:	Nickel Alloy 718 Overall
Material Document And	Ams 5596 Assn Std 1st Material Response Overall Or Ams 5597 Assn Std 2nd Material Response Overall Or Ams 5662, Nickel Alloy 718 Assn
Classification:	Std 3rd Material Response Overall
Surface Treatment:	Passivate Overall

How to Order

Order this washer from our inventory online by visiting https://military-fasteners.com/washers/flat+washers/MS14183L-12 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/washers/flat+washers/MS14183L-12 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/washers/flat+washers/MS14183L-12 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/washers/flat+washers/MS14183L-12 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/washers/ms14183L-12 and selecting the quantity you want then click "add to cart".