

Description

Hole Diameter: 5/8", Thickness: 1/8"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|--------------------|------------------|
| SKU / Model: | MS14183L9 |
| Minimum Qty (MOQ): | 5 EA |
| NSN: | 5310-01-491-4915 |



P/N MS14183L-9 Specifications

| | |
|--|--|
| Cross-sectional Shape Style: | Rectangular |
| Hole Diameter: | 0.564 Inches Minimum And 0.568 Inches Maximum |
| Peripheral Shape Style: | Round |
| Center Hole Shape Style: | 1 Round |
| Thickness: | 0.071 Inches Minimum And 0.085 Inches Maximum |
| Overall Diameter: | 1.037 Inches Minimum And 1.047 Inches Maximum |
| Hardness Rating: | 36.0 Rockwell C Minimum And 46.0 Rockwell C Maximum |
| Material: | Nickel Alloy 718 Overall |
| Material Document And Classification: | Ams 5596 Assn Std Single Material Response Overall Or Ams 5597 Assn Std Single Material Response Overall Or Ams 5662 Assn Std Single Material Response Overall |
| Surface Treatment: | Passivate Overall |

How to Order

Order this washer from our inventory online by visiting <https://military-fasteners.com/washers/flat+washers/MS14183L-9> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.