

Description

Hole Diameter: 5/8

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|---|
| SKU / Model: | MS14183LC10 |
| Minimum Qty (MOQ): | 5 |
| NSN: | 5310-01-482-6518 |
| ECCN: | EAR99 |
| National Motor Freight: | 194160, Washer Or Gaskets, Iron Or Steel, |



* See page 2 for technical characteristics

P/N MS14183L-C10 Specifications

| | |
|---|--|
| Hole Diameter: | 0.627 Inches Minimum And 0.631 Inches Maximum |
| Outside Diameter: | 1.153 Inches Minimum And 1.163 Inches Maximum |
| Recess Diameter: | 0.764 Inches Minimum And 0.774 Inches Maximum |
| Material Thickness: | 0.099 Inches Minimum And 0.119 Inches Maximum |
| Recess Angle: | 90.0 Degrees Nominal |
| Material: | Nickel Alloy 718 Overall |
| Material Document And Classification: | Ams 5596 Assn Std Single Material Response Overall Or Ams 5597 Assn Std Single Material Response Overall Or Ams 5662 Assn Std Single Material Response Overall |
| Surface Treatment: | Passivate Overall |
| Surface Treatment Document And Classification: | Qq-p-35 Fed Spec Single Treatment Response Overall |
| Style Designator: | 15 Recessed |

How to Order

Order this recessed washer from our inventory online by visiting <https://military-fasteners.com/washers/recessed+washers/MS14183L-C10> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.