

Description

Hole Diameter: 5/8

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	MS14183LC10
Minimum Qty (MOQ):	5
NSN:	5310-01-482-6518
ECCN:	EAR99
National Motor Freight:	194160, Washer Or Gaskets, Iron Or Steel,



NO IMAGE
AVAILABLE

P/N MS14183L-C10 Specifications

Hole Diameter:	0.627 Inches Minimum And 0.631 Inches Maximum
Outside Diameter:	1.153 Inches Minimum And 1.163 Inches Maximum
Recess Diameter:	0.764 Inches Minimum And 0.774 Inches Maximum
Material Thickness:	0.099 Inches Minimum And 0.119 Inches Maximum
Recess Angle:	90.0 Degrees Nominal
Material:	Nickel Alloy 718 Overall
Material Document And Classification:	Ams 5596 Assn Std Single Material Response Overall Or Ams 5597 Assn Std Single Material Response Overall Or Ams 5662 Assn Std Single Material Response Overall
Surface Treatment:	Passivate Overall
Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response Overall
Style Designator:	15 Recessed

How to Order

Order this recessed washer from our inventory online by visiting <https://military-fasteners.com/washers/recessed+washers/MS14183L-C10> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.