

**Description**

Hole Diameter: 3/8",

\* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information****Alternate Part Numbers**[MS14183-LC12](#) [MS14183LC12](#)

SKU / Model:	MS14183LC12
Minimum Qty (MOQ):	5
NSN:	5310-01-490-3137
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE  
AVAILABLE

## P/N MS14183L-C12 Specifications

<b>Hole Diameter:</b>	0.078 Inches Minimum And 0.793 Inches Maximum
<b>Outside Diameter:</b>	1.384 Inches Minimum And 1.394 Inches Maximum
<b>Recess Diameter:</b>	0.981 Inches Minimum And 0.991 Inches Maximum
<b>Material Thickness:</b>	0.099 Inches Minimum And 0.119 Inches Maximum
<b>Hardness Rating:</b>	36.0 Rockwell C Minimum Or 45.0 Rockwell C Maximum
<b>Recess Angle:</b>	44.0 Degrees Minimum And 46.0 Degrees Maximum
<b>Material:</b>	Nickel Alloy 718 Overall
<b>Material Document And Classification:</b>	Ams5596 Assn Std Single Material Response Overall Or Ams5597 Assn Std Single Material Response Overall Or Ams5662 Assn Std Single Material Response Overall
<b>Surface Treatment:</b>	Passivate Overall
<b>Surface Treatment Document And Classification:</b>	Qq-p-35 Fed Spec Single Treatment Response Overall
<b>Style Designator:</b>	Shouldered And Recessed

## How to Order

Order this recessed washer from our inventory online by visiting <https://military-fasteners.com/washers/recessed+washers/MS14183L-C12> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.