

Description

Hole Diameter: 7/8",

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	MS14183LC14
Minimum Qty (MOQ):	5
NSN:	5310-01-543-2038
ECCN:	EAR99

NO IMAGE
AVAILABLE

P/N MS14183L-C14 Specifications

Hole Diameter:	0.914 Inches Minimum And 0.918 Inches Maximum
Outside Diameter:	1.615 Inches Minimum And 1.625 Inches Maximum
Recess Diameter:	1.182 Inches Minimum And 1.192 Inches Maximum
Material Thickness:	0.137 Inches Minimum And 0.147 Inches Maximum
End Item Identification:	F-22 Raptor
Hardness Rating:	36.0 Rockwell C Minimum And 45.0 Rockwell C Maximum
Recess Angle:	45.0 Degrees Nominal
Surface Finish:	125.0 Microinches All Surfaces
Part Name Assigned By Controlling Agency:	Washer,countersunk And Plain
Material:	Nickel Alloy 718 Overall
Material Document And Classification:	Ams 5696 Assn Std Single Material Response Overall Or Ams 5597 Assn Std Single Material Response Overall Or Ams 5662 Assn Std Single Material Response Overall
Surface Treatment:	Passivate Overall Or Cadmium Overall
Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response Overall Or Cda000 Type 2, Class 2 Fed Spec Single Treatment Response Overall
Style Designator:	15 Recessed

How to Order

Order this flat washer from our inventory online by visiting <https://military-fasteners.com/washers/flat+washers/MS14183L-C14> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.